


D8C2K-28H

Spring Engaged Friction Brake
NEMA 284TC, 286TC Frame Mount



NOT suitable for pulley output

Engagement/Disengagement

Spring/Air

Facing Type

High Coefficient

Torque – Dynamic

2,367 Pound Inches

Minimum Disengagement Pressure

71 PSI

Maximum Operating Pressure

90 PSI

Maximum RPM

1,650

Input Bore/Output Shaft

1.875"

Air Volume New

0.71 Cubic Inches

Air Volume Worn

5.93 Cubic Inches

Finish


Aluminum

Clear Anodized


Enclosed

Shipping Weight

75 Pounds



TORQUE vs. AIR PRESSURE



NEW vs. BURNISHED TORQUE

The torque output of a new friction brake or clutch can be up to 40% less than the published torque rating. To achieve full design torque, a unit must be cycled under load to burnish the friction surfaces. The exact number of cycles varies by application.

When calculating required torque always use a safety factor of 1.5 to 2. It is not recommended to select a product for use at its maximum rated torque for continuous duty.

PRODUCT SELECTION

Torque capacity is only one factor to consider when making a product selection. Ensure that you will have the right product for the job by contacting our engineering department for application review and selection assistance.



101 Cummings Drive
Walton, KY 41094 USA


859-291-0849

machiii.com

engineering@machiii.com

D8C2K-28H

Parts Diagram



REF#	DESCRIPTION & PARTS INCLUDED	QUANTITY	KIT NUMBER
1	DRIVE HUB	1	D8C2K-28H-P001
	DRIVE DISC KIT		D8C2K-28H-DRDK
2	Drive Disc	1	
3	Retainer Ring	2	
	REPAIR KIT		D8C2K-28H-RPRK
4	Friction Disc	2	
5	Coil Spring	17	
6	O-Ring	2	
	PISTON KIT		D8C2K-28H-PSTK
7	Pressure Plate	1	
8	Screw	3	
9	Spacer	3	
10	Piston	1	
	CYLINDER KIT		D8C2K-28H-CYLK
11	Cylinder	1	
12	Top Plate	1	
13	Screw	8	
14	Retainer Ring	2	
15	Bearing	1	

PARTS KITS

The *Repair Kit* contains common wear items for this product. Users are encouraged to stock one or more repair kits considering the number of units installed and the potential downtime if machinery on which the unit is installed is critical equipment. To obtain current pricing and lead time for parts kits, contact customer service.

orders@machiii.com

ADDITIONAL PRODUCT INFORMATION

For illustrated guides showing how Mach III products work, selection guidelines, product manuals, and installation and use recommendations:

<https://machiii.com/resources/how-our-products-work>

For information about how to order, return policy and warranty information:

<https://machiii.com/resources/how-to-order>



859-291-0849

machiii.com

engineering@machiii.com