# Z3A1R-STH

Combination Air Engaged Friction Clutch, Air Engaged Friction Brake, Stop & Start the Shaft



#### Minimum Sprocket Sizes

Chain Size	35	40	50	60
Minimum Teeth	33	25	21	18

#### **Clutch Engagement/Brake Engagement**

Air/Air

Facing Type (Clutch & Brake)

High Coefficient

Clutch Torque @ 80 PSI (max) – Dynamic

280 Pound Inches

Brake Torque @ 80 PSI (max) – Dynamic

280 Pound Inches

#### Maximum RPM

1,750

#### Bore Range with Standard Keyway

0.625 (16) to 1.000 (24) Inches (mm)

Air Volume New (Clutch & Brake)

0.15 Cubic Inches

Air Volume Worn (Clutch & Brake)

0.95 Cubic Inches

Finish


Aluminum

**Open or Enclosed Construction** 


Open

**Shipping Weight** 

6 Pounds



## TORQUE vs. AIR PRESSURE



# **NEW vs. BURNISHED TORQUE**

The torque output of a new friction brake or clutch can be up to 40% less than the published torque rating. To achieve full design torque, a unit must be cycled under load to burnish the friction surfaces. The exact number of cycles varies by application.

When calculating required torque always use a safety factor of 1.5 to 2. It is not recommended to select a product for use at its maximum rated torque for continuous duty.


# PRODUCT SELECTION

Torque capacity is only one factor to consider when making a product selection. Ensure that you will have the right product for the job by contacting our engineering department for application review and selection assistance.



1580 Lake Street Elmira, NY 14901 USA 859-291-0849 machiii.com

engineering@machiii.com



REF#	DESCRIPTION & PARTS INCLUDED	QUANTITY	KIT NUMBER
	REPAIR KIT		Z3A1R-STH-RPRK
1	Friction Disc	3	
2	Wave Spring - Clutch	1	
3	Coil Spring - Brake	3	
4	O-Ring	4	
	DRIVE HUB KIT		Z3A1R-STH-HUBK
5	Drive Hub	1	Specify Bore Size When Ordering
6	Set Screw	2	
7	Retainer Ring	1	
	SLEEVE KIT		Z3A1R-STH-SLVK
8	Sleeve	1	
9	Bearing	2	
10	Retainer Ring	3	
	CYLINDER KIT		Z3A1R-STH-CYLK
11	Cylinder	1	Loning the liter
12	Bearing	2	
13	Retainer Ring	3	
14	PISTON - BRAKE	1	Z3A1R-STH-P0B4
14			
	PISTON KIT - CLUTCH		Z3A1R-STH-PSTK
15	Piston	1	
16	Pin	2	
17	Bearing Cone	1	
10	Screw	1	
15			
	DRIVE DISC KIT		Z3A1R-STH-DRDK
20	Drive Disc	3	
	ADAPTER KIT		Z3A1R-STH-ADPK
21	Brake Adapter	1	
22	Screw	6	

### **PARTS KITS**

The *Repair Kit* contains common wear items for this product. Users are encouraged to stock one or more repair kits considering the number of units installed and the potential downtime if machinery on which the unit is installed is critical equipment. To obtain current pricing and lead time for parts kits, contact customer service.

orders@machiii.com

# ADDITIONAL PRODUCT INFORMATION

For illustrated guides showing how Mach III products work, selection guidelines, product manuals, and installation and use recommendations:

https://machiii.com/resources/how-our-products-work

For information about how to order, return policy and warranty information:

https://machiii.com/resources/how-to-order



859-291-0849 machiii.com engineering@machiii.com